## XRD: X-ray diffraction

X-ray diffraction is analytical method based on inspection of crystalline structure of samples. Applications:

> Metallurgy, Mineralogy Powders, Pigments, Polymers Surface layers Strain mapping

## DETECTOR IS A KEY

The traditional XRD uses monochromatic X-rays which make the apparatus large and slow. ADVACAM's spectral camera based on Timepix3 chip with high resolution makes it fast and compact:

The high resolution detector can be placed close to the sample covering large solid angle -> fast data accumulation.

The polychromatic X-ray beam can be used with ADVACAM's energy dispersive detectors -> system is faster, smaller, much less complex.

Broad energy range (3 - 150 keV): Even heavy samples can be transmitted (stainless steel, heavy metals and minerals).



Image seen by detector

Recalculate & sum bins:







Silicon powder in distance of 25 mm with polychromatic X-ray beam of 0.5 x 0.5 mm at 80 kVp.





## SUITABLE CAMERAS

Readout chip type Sensor material Pixel size Readout speed Interface Dimensions Weight



MINIPIX TPX3

Timepix 3 Si or CdTe 55 x 55 um 2.35 Million hits/s USB 2.0 (High-Speed) 80 x 21 x 14 mm 30 g



ADVAPIX TPX3

Timepix 3 Si or CdTe 55 x 55 um 40 Million hits/s **USB 3.0** 125 x 79 x 25.5 mm 503 g

- ∧ D V A C A M